

```
user@ITZR-E246-Amis-64-L6 ~ $ lspci -v
00:00.0 Host bridge: Intel Corporation Atom Processor Z36xxx/Z37xxx Series SoC Transaction Register (rev 0f)
Subsystem: Device 1027:2014
Flags: bus master, fast devsel, latency 0
Kernel driver in use: iosf_mbi_pci

00:02.0 VGA compatible controller: Intel Corporation Atom Processor Z36xxx/Z37xxx Series Graphics & Display (rev 0f) (prog-if 00 [VGA controller])
Subsystem: Device 1027:2014
Flags: bus master, fast devsel, latency 0, IRQ 202
Memory at 90000000 (32-bit, non-prefetchable) [size=4M]
Memory at 80000000 (32-bit, prefetchable) [size=256M]
I/O ports at 1000 [size=8]
Expansion ROM at <unassigned> [disabled]
Capabilities: <access denied>
Kernel driver in use: i915
Kernel modules: i915

00:14.0 USB controller: Intel Corporation Atom Processor Z36xxx/Z37xxx, Celeron N2000 Series USB xHCI (rev 0f) (prog-if 30 [XHCI])
Subsystem: Intel Corporation Atom Processor Z36xxx/Z37xxx, Celeron N2000 Series USB xHCI
Flags: bus master, medium devsel, latency 0, IRQ 200
Memory at 90800000 (64-bit, non-prefetchable) [size=64K]
Capabilities: <access denied>
Kernel driver in use: xhci_hcd
Kernel modules: xhci_pci

00:1a.0 Encryption controller: Intel Corporation Atom Processor Z36xxx/Z37xxx Series Trusted Execution Engine (rev 0f)
Subsystem: Intel Corporation Atom Processor Z36xxx/Z37xxx Series Trusted Execution Engine
Flags: bus master, fast devsel, latency 0, IRQ 203
Memory at 90700000 (32-bit, non-prefetchable) [size=1M]
Memory at 90600000 (32-bit, non-prefetchable) [size=1M]
Capabilities: <access denied>
Kernel driver in use: mei_txe
Kernel modules: mei_txe

00:1f.0 ISA bridge: Intel Corporation Atom Processor Z36xxx/Z37xxx Series Power Control Unit (rev 0f)
Subsystem: Intel Corporation Atom Processor Z36xxx/Z37xxx Series Power Control Unit
Flags: bus master, medium devsel, latency 0
Capabilities: <access denied>
Kernel driver in use: lpc_ich
Kernel modules: lpc_ich

user@ITZR-E246-Amis-64-L6 ~ $
```